

# PRODUCT INFORMATION

**PART NUMBER:**

Varies with colour and packing.

**DESCRIPTION:**

Circular 10-core: 1 x 2mm<sup>2</sup> (28/0.3mm) + 9 x 1mm<sup>2</sup> (32/0.2mm); Plain Copper, TWA PVC Insulated, HR PVC Sheathed.

**CONDUCTORS:**

Plain annealed copper bunch meeting the requirements of ISO 6722.  
9 cores, 1mm<sup>2</sup> (32/0.2mm).  
1 core, 2mm<sup>2</sup> (28/0.3mm).

**INSULATION:**

"Thin wall auto grade" PVC compound, formulated without lead based additives meeting the requirements of ISO 6722, Class B.  
Minimum thickness (1mm<sup>2</sup>) = 0.24mm;  
(2mm<sup>2</sup>) = 0.28mm.

**LAY UP:**

Centre: White (2mm<sup>2</sup>), Black (1mm<sup>2</sup>).  
Outer: (1mm<sup>2</sup>), Red, (Dark) Green, Grey, Blue, Yellow, Brown, Orange, Violet.

**SCREEN:**

Not Applicable.

**SHEATH:**

PVC compound, formulated without lead based additives meeting the requirements of ISO 6722, Class A.  
Minimum overall diameter = 9.5mm.  
Maximum overall diameter = 10.2mm.

**SERVICE DATA:**

For use in road vehicles.  
Maximum Rated Voltage: 60V d.c. or 25V a.c.  
Maximum conductor operating temperature: 100°C.  
Minimum operating temperature: -40°C.  
Approximate Mass/Unit Length: 177kg/km.